

Combination Sander Safety Test

Name: _____ Date: _____ Class: _____

Multiple Choice – Circle the letter of the most correct answer.

1. How far away from the sanding belt/disc should the table be?
 - a. 1/16 inch away
 - b. 1/8 inch away
 - c. 1/4 inch away
 - d. 1/2 inch away
2. The only safe place to sand your stock on the disc sander is on the:
 - a. Left side
 - b. Upward side
 - c. Downward side
 - d. Right side
3. When using the oscillating spindle sander, it is important to remember to keep hold of your stock and:
 - a. That you do not have to use a insert at all
 - b. Always us the correct size insert for the size spindle
 - c. If there is a insert that is in the table that is good enough
 - d. The bigger the insert the better
4. It is only safe to leave to walk away from the machine when:
 - a. The power is off
 - b. The power is on
 - c. The power is off and the sanders have stopped
 - d. The power is off and the sander is slowing down

Jig saw Safety Test

1. The safe distance for the foot to be from your stock is:
 - a. On the stock
 - b. 1/16 inch away
 - c. 1/8 inch away
 - d. 1/4 inch away
2. When cutting on the Jig saw a _____ pressure is the only safe pressure to use:
 - a. Fast, hard pressure
 - b. Light pressure and to keep the stock moving
 - c. Once fast push
 - d. Light pressure and allow the stock to stop moving
3. If a blade brakes, you need to:
 - a. Stop and find another saw
 - b. Try and get the blade to work again
 - c. Try and remove the blade with the machine on and on low speed
 - d. Stop, unplug the machine, replace blade, test blade, and continue work